



# TM Palletizing Operator

**WORLD  
NO. 1**

- 17 Certified PL=d Cell Level Safety Functions
- Start to Palletize in 5 Minutes!
- TMstudio Palletizing Wizard: palletizing wizard and collision detection




## TM Operator

**Click & Run, Cheer & Apply**

### What is TM Operator?

- A ready to use, all-in-one application based robot cell.
- With application based software.
- Reduce programming effort.
- Start to work within 5~10 minutes.




# Application Based Software

## TMstudio Palletizing Wizard

Provide the optimization solution for palletizing.

- Customize box, pallet size
  - Regular Palletizing for same boxes
  - Palletizing for different pallets of boxes
  - Regular De-Palletizing for same boxes
  - De-Palletizing for different pallets of boxes
  - Change Pallet
- Generate point file offline.
- Custom box arrangement and sequence.
- Palletizing simulation and collision detection.






## Software packages for TMflow™

### Main Function

- Calibration of pillar. (fig. A)
- Main function based on file generated from TMstudio Palletizing Wizard, and settings for the cell. (fig. B)

### Flexibility for functional expansion by user

- Using customized gripper.
- Adding more vision functions like barcode reading.
- Adding downward sensor detection before releasing the box.
- Slip sheet application programming .



# Specification

Specification	TM Palletizing Operator-TM12
Stack Height*	General 1200mm, Max. 1900mm
Maximum Payload*	10kg
Maximum Pallet Speed	Up to 7 boxes/object per minute
Certification	CE, Machine Directive 2006/42/EC, ISO 12100, EN 60204-1, ISO 10218-2 (partly completed machinery), ISO 13849-1, ISO/TS 15066
Safety Functions	17 cell level safety functions with 3rd Party certification PL=d according to ISO13849-1
Teach Pendant	10.1" capacitive touch screen, with ESTOP and Enabling Switch, Cable length: 3m, 2 USB ports provided
IP Rating	IP54 for Robot Arm, IP65 for Teach Pendant, IP 32 for Gripper and rest parts
Interface	Support multiple safety inputs and safety outputs: emergency stop, safeguard pause, Safeguard Human-Machine Safety Setting
Software	Offline programming & Simulation: TMstudio Palletizing Wizard etting and Running: TM Palletizing Operator Software Packages
Eye in Hand(Built in)	1.2M/5M pixels, color camera
Eye to Hand(Optional)	Support Maximum 2 GigE cameras

\*The maximum stack height indicates the use case of single-box stack within proximity. In the use case of maximum pallet size(1219mm×1016mm), it can generally reach 1,200 mm. Differences in box size, box layout and gripper might affect actual stack height

\*The payload at robot flange is 12kg.

# Product Content

Item	Standard Package
TM12 robot Arm & control box	✓
Teach Pendant and cable	✓
TM Palletizing Operator Base, including -Indication light for Pallet detection -Lifting Pillar module & Drag Chain	✓
Pneumatic Suction Gripper Set, including -Pneumatic Suction Gripper -Pneumatic Set: Air preparation unit, Solenoid valve, Air tube to the tool end -Cable Conduit	✓
Software License Dongles 1 for TMstudio Palletizing Wizard 1 for TM Palletizing Operator Software Packages	✓